



Hire & Sales

PORTABLE COOLING HEATING VENTILATION DRYING EQUIPMENT



1300 885 188

MELBOURNE SYDNEY BRISBANE ADELAIDE PERTH

NATIONAL COVERAGE AUSTRALIA WIDE

REFRIGERATED SPOT COOLERS

Spot coolers provide cold air flow with easy mobility and low noise output. From 4.4kW to 21.5kW. They are ideal for server rooms, offices, commercial, workshop and industrial applications. The flexible ducts direct controlled powerful air flow.

CB4400 Spot Cooler Reverse Cycle - 4.4kW



Model No.	CB4400 (Reverse Cycle)
Cooling Capacity	4.4kW
Heating Capacity	4.7kW
Power Supply	240v/10a
Current Consumption	9.5a
Air Flow - Evap.m³/hr	450
Exhaust Duct Diameter	150mm
Exhaust Duct Length	3m (max)
Noise Level	56dB(A)
Dimensions (WxDxH)	471 x 355 x 850mm
Weight	34.5kg
Coverage	20-27m²

CB12000 Reverse Cycle Spot Cooler - 12kW



Model No.	CB12000
Cooling Capacity	12kW
Power Supply	240v/23a, 1-Phase
Current Consumption	21.4a
Air Flow - Evap.m³/hr	1,860
Exhaust Duct Diameter	500mm
Exhaust Duct Length	10m (max)
Noise Level	70dB(A)
Dimensions (WxDxH)	740 x 1450 x 1212mm
Weight	200kg
Coverage	120m²

Movin Cool Spot Cooler - 4.5kW



Model No.	MC4500
Cooling Capacity	4.5kW
Power Supply	240v/10a
Current Consumption	6.7a
Power Consumption	1.5kW
Air Flow - Evap.m³/hr	800
Exhaust Duct Diameter	300mm
Exhaust Duct Length	10m (max)
Noise Level	64dB(A)
Dimensions (WxDxH)	491 x 672 x 1050mm
Weight	76kg
Coverage	40-50m²

CB17000 Spot Cooler - 17.5kW



Model No.	CB17000
Cooling Capacity	17.5kW
Power Supply	415v/32a, 3-Phase
Current Consumption	13a
Air Flow - Evap.m³/hr	2,400
Exhaust Duct Diameter	400mm
Exhaust Duct Length	10m (max)
Noise Level	72dB(A)
Dimensions (WxDxH)	740 x 1400 x 1516mm
Weight	250kg
Coverage	160m²

CB4900 Spot Cooler - 4.9kW



Model No.	CB4900
Cooling Capacity	4.9kW
Power Supply	240v/10a
Current Consumption	9.8a
Power Consumption	2.15kW
Air Flow - Evap.m³/hr	660-780
Exhaust Duct Diameter	350mm
Exhaust Duct Length	10m (max)
Noise Level	68dB(A)
Dimensions (WxDxH)	490 x 600 x 1303mm
Weight	86kg
Coverage	50m²

CB20000 Spot Cooler - 21.5kW



Model No.	CB20000
Cooling Capacity	21.5kW
Power Supply	415v/32a, 3-Phase
Current Consumption	17.4a
Air Flow - Evap.m³/hr	3,060
Exhaust Duct Diameter	500mm
Exhaust Duct Length	10m (max)
Noise Level	73dB(A)
Dimensions (WxDxH)	740 x 1670 x 1212mm
Weight	300kg
Coverage	200m²

CB7300 Spot Cooler - 7.3kW



Model No.	CB7300
Cooling Capacity	7.3kW
Power Supply	240v/15a
Current Consumption	13a
Power Consumption	2.6kW
Air Flow - Evap.m³/hr	840-960
Exhaust Duct Diameter	350mm
Exhaust Duct Length	10m (max)
Noise Level	69dB(A)
Dimensions (WxDxH)	490 x 600 x 1303mm
Weight	90kg
Coverage	50-70m²

SPOT COOLER INSTALLATION

The typical installation of our Spot Cooler range involves the installation of the exhaust duct (Warm Air) to be positioned into the roof space via the false ceiling tile, alternatively the exhaust duct can be run out a doorway or window. Call to discuss a solution to suit your onsite requirements.



CONDENSATE PUMP KIT

CB4900 & CB7300 Spot Coolers.
The condensate pump kit is available as an alternative to the condensate bucket. Ideally suited where continuous operation is required.



PORTABLE SPLIT SYSTEMS

PORTA TEMP 4500A

Model No.	4500A
Cooling Capacity	4.5kW
Power Supply	240v/10a
Current Consumption	7.6a
Air Flow - Evap.m³/hr	800
Exhaust Duct Diameter (WxH)	200 x 100mm
Exhaust Duct Length	5m (max)
Noise Level	54dB(A)
Dimensions (WxDxH)	695 x 458 x 954mm
Weight	95kg
Coverage	40m²



PORTA TEMP 4500W

Model No.	Porta-Temp 4500W
Cooling Capacity	4.5kW
Power Supply	240v/10a
Current Consumption	7.3a
Air Flow - Evap.m³/hr	715
Hose Length	5m (Max 30m)
Noise Level	54dB(A) (Indoor Unit)
Dimensions Indoor Unit (WxDxH)	695 x 330 x 954mm
Dimensions Condenser (WxDxH)	560 x 280 x 520mm
Weight	105/20kg
Coverage	45m²



PAC 22

Model No.	PAC 22
Cooling Capacity	6.5kW
Power Supply	240v/15a
Current Consumption	11a
Air Flow - Evap.m³/hr	990
Hose Length	5m (Max 30m)
Noise Level	54dB(A) (Indoor Unit)
Dimensions Indoor Unit (WxDxH)	1,240 x 850 x 380mm
Dimensions Condenser (WxDxH)	520 x 560 x 280mm
Weight	110/20kg
Coverage	70m²



EVAPORATIVE COOLERS

CB07EQ



Model No.	CB07EQ
Power Supply	240v/10a
Current Consumption	1.3a
Air Flow - m³/hr	7,600
Noise Level	62dB(A)
Water Tank	120 Litres
Direct Hose Connection	Yes
Fan Speed Setting	x 3
Water Consumption	6-15 Litres Per Hour
Dimensions (WxDxH)	910 x 480 x 1350mm
Weight	29kg/149kg
Coverage	40m²

CB14000



Model No.	CB14000
Power Supply	240v/10a
Current Consumption	2.6a
Air Flow - m³/hr	15,200
Noise Level	66dB(A)
Water Tank	120 Litres
Direct Hose Connection	Yes
Fan Speed Setting	x 3
Water Consumption	3-6 Litres Per Hour
Dimensions (WxDxH)	910 x 490 x 2190mm
Weight	64kg/184kg
Coverage	120m²

CB18IQ



Model No.	CB18IQ
Power Supply	240v/10a
Current Consumption	7.5a
Air Flow - m³/hr	18,000
Noise Level	68dB(A)
Water Tank	300 Litres
Direct Hose Connection	Yes
Fan Speed Setting	x 50
Water Consumption	5-20 Litres Per Hour
Dimensions (WxDxH)	1080 x 1160 x 1730mm
Weight	95.5kg/395.5kg
Coverage	150m²

CB40IQ



Model No.	CB40IQ
Power Supply	240v/10a
Current Consumption	7.5a
Air Flow - m³/hr	40,000
Noise Level	66dB(A)
Water Tank	260 Litres
Direct Hose Connection	Yes
Fan Speed Setting	x 50
Water Consumption	5-20 Litres Per Hour
Dimensions (WxDxH)	1950 x 765 x 2040mm
Weight	197kg/457kg
Coverage	300m²

REVERSE CYCLE PACKAGE AIR CONDITIONING

Cool Breeze Rentals offer a wide range of Reverse Cycle Packaged Air Conditioners to ensure the right fit for every project. They are available with skid bases for forklifts and cranes, external isolators and plugs for fast easy connections and lower capacity compact sizes. Some models are also available not only in horizontal but also vertical discharge to assist with limited site space, all while achieving your required capacity. From events, shopping centres, warehouses, data centres, retail spaces, service stations and many more, Cool Breeze Rentals have the equipment, accessories and expertise to provide the solution to your air conditioning requirements.



Cooling Capacity (kW)	Air Discharge	Power Draw (F.L.A) @ 415	Air Flow (l/s)	Dimensions -Unit Only (L X W X H - mm)	Estimated Weight (kg)
20kW	Horizontal	15a	1,111	1700 x 1200 x 1060	550kg
28kW	Horizontal	20a	1,444	1580 x 870 x 1900	700kg
28kW	Vertical	20a	1,444	1600 x 1200 x 2230	700kg
35kW	Horizontal	28a	1,667	2040 x 1270 x 1230	800kg
64kW	Horizontal	40a	3,611	2500 x 1900 x 1350	1450kg
64kW	Vertical	40a	3,611	2120 x 1887 x 2536	1600kg
83kW	Vertical	57a	5,278	2230 x 2030 x 2580	1850kg
100kW	Horizontal	65a	5,300	2900 x 2400 x 1920	1800kg
125kW	Horizontal	83a	6,700	3000 x 2300 x 2660	1950kg
160kW	Horizontal	95a	8,500	3000 x 2300 x 2660	2300kg

CHILLERS & AIR HANDLING UNITS

The Cool Breeze Rentals range of temporary Air Cooled Fluid Chillers, Air Handling Units and Ancillary Equipment is offered to cater for your specific needs. Temporary Chiller and Air Handler hire is made easy with touch pad control panels and a complete range of accessories covering ducting, fluid hoses and pumps, all backed with dedicated 24/7 service. Whether your requirements are for air conditioning breakdowns, supplementary cooling, scheduled maintenance, short term event requirements or even as stand-by back up, Cool Breeze Rentals can provide short term and long term hires with customised equipment configurations.



Air Cooled Chiller	Length	Width	Height	Power Supply
180kW	2290mm	2190mm	2480mm	116a / 415v
250kW	3270mm	2190mm	2480mm	151a / 415v

AHU	Length	Width	Height	Power Supply
100kW	1440mm	700mm	2180mm	3phase / 9.5a
120kW (in frame)	2290mm	1130mm	2500mm	3phase / 13a
120kW	1920mm	1000mm	2180mm	3phase / 13a

FANS

PEDESTAL FAN

Model No.	CBPF650
Power Supply	240v/10a
Current Consumption	1.2a
Air Flow - m³/h	5,400
Noise Level	67d(B)A
Fan Blade Diameter	650mm
Height	1750mm
Weight	30kg
Coverage	20m²



MISTING FAN

Model No.	CBMF610
Power Supply	240v/10a
Current Consumption	1.86a
Air Flow - m³/h	11,700
Noise Level	68d(B)A
Fan Blade Diameter	610mm
Water Tank	30 Litres
Water Consumption	5 Litres Per Hour
Height	1936mm
Weight	25kg/55kg
Coverage	40m²



MISTING FAN

Model No.	CBMF20
Power Supply	240v/10a
Current Consumption	1a
Air Flow - m³/h	11,400
Noise Level	68d(B)A
Fan Blade Diameter	500mm
Water Tank	14 Litres
Water Consumption	2.8 Litres Per Hour
Height	1685mm
Weight	25kg/39kg
Coverage	30m²



MISTING FAN

Model No.	CBMF26
Power Supply	240v/10a
Current Consumption	1.1a
Air Flow - m³/h	13,200
Noise Level	68d(B)A
Fan Blade Diameter	650mm
Water Tank	23 Litres
Water Consumption	5 Litres Per Hour
Height	1930mm
Weight	32kg/55kg
Coverage	40-80m²



MANCOOLER FANS



Model No.	CBMC300
Power Supply	240v/10a
Current Consumption	2.1a
Air Flow - m³/h	4,600
Noise Level	69d(B)A
Diameter (mm)	300
Weight	10kg



Model No.	CBMC500
Power Supply	240v/10a
Current Consumption	4.6a
Air Flow - m³/h	8,700
Noise Level	73d(B)A
Diameter (mm)	500
Weight	37kg



Model No.	CBMC600
Power Supply	240v/10a
Current Consumption	7.5a
Air Flow - m³/h	14,400
Noise Level	77d(B)A
Diameter (mm)	600
Weight	67.5kg



Model No.	CBMC800
Power Supply	240v/10a
Current Consumption	1.5a
Air Flow - m³/h	9,900
Noise Level	65d(B)A
Diameter (mm)	800
Weight	49kg



Model No.	CBMC1050
Power Supply	240v/10a
Current Consumption	3.6a
Air Flow - m³/h	14,700
Noise Level	70d(B)A
Diameter (mm)	1,050
Weight	80kg

FLOOD RESTORATION

AIRMOVER/ CARPET DRYER



Model No.	AIRMOVER/CARPET DRYER
Power Supply	240v/10a
Current Consumption	5a
Air Flow (Max Speed)	6,200cm/h
Fan Speed (Max Speed)	1400rpm
Fan Speed Setting	x 3
Dimensions (WxDxH)	500x500x545mm
Weight	17kg

CBDH20 DEHUMIDIFIER



Model No.	CBDH20 Dehumidifier
Power Supply	240v/10a
Rated Current	1.6a
Air Flow - m³/hr	160
Temperature Operating Range	5° C - 35° C
Moisture Removal Max.	20L/day (30° C RH80%)
Moisture Removal Nom.	12L/day (27° C RH60%)
Water Tank Capacity	5.5 Litres
Dimensions (WxDxH)	385x290x595mm
Weight	13.2kg

CBDH55 DEHUMIDIFIER



Model No.	CBDH55 Dehumidifier
Power Supply	240v/10a
Rated Current	3.2a
Air Flow - m³/hr	350
Temperature Operating Range	5° C - 35° C
Moisture Removal Max.	55L/day (30° C RH80%)
Moisture Removal Nom.	30L/day (27° C RH60%)
Drain Hose Length	4.5 Metres
Dimensions (WxDxH)	545x500x638mm
Weight	39kg

CBDH85 DEHUMIDIFIER



Model No.	CBDH85 Dehumidifier
Power Supply	240v/10a
Rated Current	4.7a
Air Flow - m³/hr	700
Temperature Operating Range	5° C - 35° C
Moisture Removal Max.	85L/day (30° C RH80%)
Moisture Removal Nom.	50L/day (27° C RH60%)
Drain Hose Length	4.5 Metres
Dimensions (WxDxH)	515x530x830mm
Weight	45kg

ADH1000 DEHUMIDIFIER



Model No.	ADH1000 Dehumidifier
Power Supply	240v/10a
Rated Current	9.7a
Air Flow - m³/hr	1,080
Temperature Operating Range	5° C - 35° C
Moisture Removal Max.	120L/day (30° C RH80%)
Moisture Removal Nom.	80L/day (27° C RH60%)
Drain Hose Length	4.5 Metres
Dimensions (WxDxH)	506x552x995mm
Weight	60kg

ELECTRIC HEATING

Electric 2kW Micro Heaters



Model No.	MF2000
Power Supply	240v/10a
Heating Capacity	2kW
Current Consumption	8.3a
Fan Speed Settings	x 5
Tip Over Switch	Yes
Noise Level	56dB(A)
Dimensions (WxDxH)	200 x 150 x 200mm
Weight	1.8kg
Coverage	20m ²

PT2400 Electric 2.4kW Radiant Heater



Model No.	PT2400
Power Supply	240v/10a
Heating Capacity	2.4kW
Current Consumption	9.5a
Heat Settings	x 2
Stand Option	Tall or Short
Noise Level	56dB(A)
Dimensions (WxDxH)	340 x 120 x 420mm
Weight	4.5kg
Coverage	20m ²

Electric Fan Forced Tiger Heaters



Model No.	P93	P153
Power Supply	415v/20a (3 Phase)	415v/32a (3 Phase)
Heating Capacity	9kW	15kW
Current Consumption	13.1a	21.9a
Air Flow - Evap.m ³ /hr	720	1,120
Noise Level	44dB(A)	47dB(A)
Dimensions (WxDxH)	530 x 350 x 480mm	510 x 410 x 530mm
Weight	10.2kg	15.9kg
Coverage	70-90m ²	120-150m ²

Electric Fan Forced Tiger Heaters



Model No.	P203	P303
Power Supply	415v/32a (3 Phase)	415v/50a (3 Phase)
Heating Capacity	20kW	30kW
Current Consumption	29.5a	44a
Air Flow - Evap.m ³ /hr	2,600	2,600
Noise Level	60dB(A)	62dB(A)
Dimensions (WxDxH)	630 x 600 x 590mm	630 x 600 x 590mm
Weight	25.5kg	29.5kg
Coverage	150-200m ²	250-300m ²

CBHB21 Electric Fan Forced Heater



Model No.	CBHB21
Power Supply	415v/32a (3 Phase)
Heating Capacity	21kW
Current Consumption	29.2a
Air Flow - Evap.m ³ /hr	1,656
Noise Level	60dB(A)
Dimensions (WxDxH)	480 x 660 x 700mm
Weight	50kg
Coverage	200m ²

DIESEL HEATING - NEW DESIGNER RANGE

DIESEL HEATERS



Model No.	CBAH300	CBAH600	CBAH800
Heating Capacity	12.7-15.1kW	16.3-18.6kW	21-23.3kW
Power Supply	240v/10a	240v/10a	240v/10a
Current Consumption	1a	1a	1a
Fuel Type	Diesel	Diesel	Diesel
Fuel Consumption	1.05-1.24 Litres Per/hr	1.33-1.52 Litres Per/hr	1.71-1.9 Litres Per/hr
Fuel Tank Capacity	45 Litre	45 Litre	70 Litre
Noise Level	48dB(A)	48dB(A)	48dB(A)
Safety	12 point system	12 point system	12 point system
Dimensions (WxDxH)	950 x 305 x 1000mm	950 x 305 x 1120mm	1300 x 350 x 1370mm
Weight	41/86kg	48/93kg	65/135kg
Coverage	91-108m ²	125-141m ²	182-216m ²

GAS HEATING

LPG PATIO HEATER

Model No.	Patio Heater
Heating Capacity	11.2kW
Mj/Hr	40.5
BTU's	38,386
Gas Consumption	8-10 Hours (9kg bottle)
Dimensions	2,250mm Tall
Weight	22kg
Coverage	20m ²



LPG PYRAMID HEATER

Model No.	Pyramid Heater
Heating Capacity	11.2kW
Mj/Hr	40.3
BTU's	38,215
Gas Consumption	8-10 Hours (9kg bottle)
Dimensions	2,200mm Tall
Weight	23kg
Coverage	20m ²



LPG RADIANT HEATERS

Model No.	GM12
Heating Capacity	6.72kW
Mj/Hr	24.2
BTU's	22,937
Gas Consumption	20/100 (Per/Hr - 9kg/45kg bottle)
Dimensions	1,800-2300mm Tall
Weight	18kg
Coverage	25m ²

Model No.	GM16
Heating Capacity	8.55kW
Mj/Hr	30.8
BTU's	29,192
Gas Consumption	14/70 (Per/Hr - 9kg/45kg bottle)
Dimensions	1,800-2300mm Tall
Weight	19kg
Coverage	33m ²



LPG JETFIRE HEATERS

Model No.	J25	J33
Power Supply	240v/10a	240v/10a
Heating Capacity	29kW	38kW
Current Consumption	1a	1a
BTU's	100,000	132,000
Air Flow - m ³ /hr	700	850
Dimensions (WxDxH)	330 x 670 x 520mm	330 x 730 x 520mm
Weight	15kg	16.45kg
Coverage	150m ²	200m ²



CONTACT DETAILS



1300 885 188

(Australia Wide)

sales@coolbreeze.net.au

www.coolbreeze.net.au

VIC -
31 Technology Circuit,
Hallam
VIC 3803

NSW -
3/16-28 Martha St
Granville
NSW 2142

QLD -
2-12 Nealdon Dve
Meadowbrook
QLD 4131

SA -
2/10-12 Carsten Rd
Gepps Cross
SA 5094

WA -
40 Sorbonne Crescent
Canning Vale
WA 6155

AGENTS

Tasmania Canberra Newcastle Rockhampton Mackay Townsville Cairns